

संख्या. पी-63013/107/02/2026/मोड-1/सी0सु0बल/ 1914-18

भारत सरकार, गृह मंत्रालय
महानिदेशालय सीमा सुरक्षा बल
(रसद निदेशालय: आधुनिकीकरण सैल)
(Email-comdtord@bsf.nic.in)

ब्लाक संख्या . 10,
सीजीओ काम्पलैक्स,
लोधी रोड, नई दिल्ली-03
दिनांक 20 अगस्त 2026


वरिष्ठ तकनीकी निदेशक
The Senior Technical Director
राष्ट्रीय सूचना-विज्ञान केन्द्र, नोर्थ ब्लॉक,
गृह मंत्रालय, नई दिल्ली
NIC, North Block, MHA
New Delhi
(द्वारा ई-मेल)
(ई-मेल पता : mpsugandhi@nic.in)

Sub: **Request for comments of stakeholders/OEM on draft QRs & TDs**

कृपया गृह मंत्रालय के पत्र संख्या IV-24011/12/2011-Prov-I(part)(CFN 3300890)-
1710 दिनांक 31st Aug 2015 के सन्दर्भ में।

2. उपरोक्त विषयान्तर्गत सूचित किया जाता है कि तकनीकी विशेषज्ञों के उप समूह द्वारा "X-Ray Baggage Inspection System (Small Size)- Revesion" के गुणात्मक आवश्यकता/परीक्षण निर्देशों के मसौदे का प्रारूप दिनांक 30 जुलाई 2026 को आयोजित सभा के दौरान तैयार किया गया, जिसको इस आशय से प्रेषित किया जा रहा है कि उक्त उपकरण के गुणात्मक आवश्यकता/परीक्षण निर्देश को गृह मंत्रालय की वेबसाइट पर 15 दिन के लिए अपलोड करने का श्रम करें।

संलग्न: उपरोक्तनुसार


(कपिल चाहर)

उप कमाण्डेंट (मोड)

प्रतिलिपि :-

1. SO (IT), North Block, MHA
(Through E-mail)
(E-mail address: soit@nic.in)

2. IT Wing, FHQ BSF

: उपरोक्त उपकरण के गुणात्मक आवश्यकता /परीक्षण निर्देशों के मसौदा को आपके सूचनार्थ एवं अग्रिम कार्यवाही हेतु प्रेषित किया जाता है।

: उपरोक्त उपकरण के गुणात्मक आवश्यकता /परीक्षण निर्देशों के मसौदे को सीमा सुरक्षा बल की वेबसाइट पर 15 दिन के लिए अपलोड करने का श्रम करें। आपसे अनुरोध है कि उक्त मसौदे को गृह मंत्रालय की वेबसाइट पर भी अपलोड करने हेतु निम्नलिखित पतों पर ई-मेल करने का श्रम करें:-

(a) Technical Director, NIC, North Block, MHA

(E-mail : mpsugandhi@nic.in)

(b) SO (IT), North Block, MHA

(E-mail : soit@nic.in)

3. ACP, Delhi Police HQr,
Jai Singh Road, New Delhi-110001
E- mail: acp.hdqr@delhipolice.gov.in
4. File.

: आपके मुख्यालय के पत्र संख्या 24206 दिनांक 30.03.2026 के संदर्भ में सूचनार्थ हेतु।



भारत सरकार, गृह मंत्रालय
महानिदेशालय सीमा सुरक्षा बल
(रसद निदेशालय: आधुनिकीकरण सैल)
ब्लाक संख्या . 10, सीजीओ काम्पलेक्स, लोधी रोड, नई दिल्ली-03
(Email-comdtord@bsf.nic.in)

संख्या. पी-63013/107/02/2026/मोड-1/सीसुबल/

दिनांक ____ अगस्त 2026

विषय : “X-Ray Baggage Inspection System (Small Size)- Revision” के गुणात्मक आवश्यकता/परीक्षण निर्देशों पर हितधारकों/निर्माताओं/विक्रेताओं की टिप्पणी के लिए अनुरोध।

“X-Ray Baggage Inspection System (Small Size)- Revision” के गुणात्मक आवश्यकता और परीक्षण निर्देशों को परिशिष्ट 'ए' के रूप में संलग्न किया गया है। हितधारकों/निर्माताओं/विक्रेताओं से अनुरोध किया जाता है कि वे उस उत्पाद की विस्तृत एवं स्टीक जानकारी दें। साथ ही प्रत्येक पैरामीटर के अनुरूप अपने उत्पाद के सही विवरणों को प्रस्तुत करें। सिर्फ 'अनुपालना' या 'अनुपालना नहीं' वाली टिप्पणी स्वीकार नहीं की जाएगी।

- क्या आप मूल उपकरण निर्माता/विक्रेता हैं?
- यदि विक्रेता मूल उपकरण निर्माता का विवरण देता है।
- मूल उपकरण निर्माता से प्राधिकरण प्रमाण पत्र।
- उत्पाद की मूल सूची।
- उत्पाद ब्रोशर एवं साहित्य रचना का ब्यौरा

1. आवश्यक जानकारी/विवरण 03 सितम्बर 2026 तक निम्नलिखित पते पर भेजे जा सकते हैं।

रसद निदेशालय, सीमा सुरक्षा बल
लेवल-8, ब्लाक-10,
केन्द्रीय कार्यालय परिसर, लोधी रोड,
नई दिल्ली-110003
ईमेल:- comdtord@bsf.nic.in

2. शीघ्र प्रतिक्रिया का अनुरोध किया जाता है।

कपिल चाहर
28/08/26
(कपिल चाहर)

उप कमाण्डेंट (आधुनिकीकरण)

GOVERNMENT OF INDIA
Ministry of Home Affairs
Directorate General Border Security Force
(Prov Dte: Mod Cell)
Block No.10, CGO Complex, Lodhi Road, New Delhi-03
(Fax: 011-24367683, Email-comdtord@bsf.nic.in)

No. P-63013/107/02/2026/Mod-I/BSF/

Dated, the __Aug 2026

Subject : Request for comments of stakeholders/OEM/Firms on QRs (Qualitative Requirements) & TDs (Trial Directives) of "X-Ray Baggage Inspection System (Small Size)- Revision"


The draft QRs/TDs "X-Ray Baggage Inspection System (Small Size)- Revision" is attached as **Appendix 'A'**. The OEMs/Vendors are requested to forward information of the product, which they can offer and also forward correct specifications of their system against each parameter. Only complied or not complied remarks will not be accepted. The firms are also requested to furnish the following details:-

- Whether you are OEM/Vendor?
- If vendor details of OEM.
- Authorization certificate from OEM.
- Original catalogue of the product
- Brochure/Literature of the product

2. The required information/details may please be forwarded at the following addresses by 03.09.2026.

Directorate General BSF,
Level-8, Block No. 10,
CGO Complex, Lodhi Road,
New Delhi-110003
Email: comdtord@bsf.nic.in

3. An early response is requested.


(**Kapil Chahar**)
Dy. Commandant (Mod)

DRAFT QRs & TDs OF X-RAY BAGGAGE INSPECTION SYSTEM (SMALL SIZE)- REVISION.

Sl. No	Revised Technical Specifications	Trial Directives	Remarks
1.	Tunnel Size - Minimum 60 cm W (width) x Minimum 40 cm H (Height) or better.	To be physically checked by the BOO through measuring instrument.	
2.	Conveyor belt speed should be between 0.18 and 0.3 meter per second. Conveyor movement bidirectional.	To be physically checked by the BOO through Tachometer.	
3.	All machines should operate on 230 VAC, 50 Hz power supply and should be able to withstand voltage fluctuations in the range of 170V to 260 V. Single Phase, 3 to 5 Amp.	Plug the machine through electrical component and check the operation of the machine within the specified range of power supply.	
4.	Conveyor Capacity- 160 kg or more	To be physically checked,	
5.	Through put should be 200 bags per hour or more	To be physically checked,	
6.	Sensors > 1000 diodes, L-shaped detector (Folded array type), In case of defective diode arrays, scanning should be disabled and error message should be displayed on the screen.	To be physically checked,	
7.	X-Ray Voltage - Maximum 160 kV	Plug the machine through electrical component and verify the X-Ray voltage on the screen of VDU.	
8.	X-Ray Source/Generator – It should be capable to operate smoothly for a period of at least six years.	An OEM certificate be obtained from the Vendor.	
9.	Duty Cycle - 100%	An OEM certificate be obtained from the Vendor.	
10.	The X-ray beam divergence should be such that the complete image at maximum size of bag is displayed without corner cuts.	Place the baggage in the tunnel of machine and see the image on VDU.	
11.	The radiation level should not exceed accepted health standard (0.1m R/Hr at a distance of 5 CM from external housing). Relevant certificate from AERB.	An AERB certificate should be obtained from the Vendors.	
12.	The operating temperature normally should be 0 deg C to 40 deg C.	NABL certificate be obtained from the Vendor.	
13.	Storage temperature 0 degree C to 50 degree C.	NABL certificate be obtained from the Vendor.	
14.	Humidity- 90% non-condensing	NABL certificate be obtained from the Vendor.	
15.	Resolution: The machine should be able to display	Scan the CTP in operational condition of	

Sl. No	Revised Technical Specifications	Trial Directives	Remarks
	single un-insulated tinned copper wire of 42-SWG or 38-AWG. All penetration and resolution condition should be met without pressing any functional key and should be online.	machine without operating any functional key, thereafter 42-SWG or 38-AWG wire should be seen on the VDU.	
16.	Penetration should be 35 mm thickness of steel or more.	Scan the CTP in operational condition of machine and see the image of 35 mm thickness of steel on VDU.	
17.	Continuous Electronic Zoom facility should be available to magnify the chosen area of an image eight times (8X) or more. Image features shall be keyboard controllable.	Scan the baggage and zoom in the facility eight times or more through zoom key from the key board.	
18.	Video display- 18.5" or better LCD Monitor SVGA High resolution, low radiation, flicker free, resolution at least 1280 x 1024, 24 bit colour real time processing.	To be checked through the technical literature.	
19.	The machine should have features of Multi-energy X-ray imaging facility where materials of different atomic number will be displayed in different colours to distinguish between organic and inorganic materials. With this method to distinguish high density organic materials including explosives. Machine should have variable colour or materials stripping to facilitate the operator to monitor images of organic materials for closer scrutiny. All suspicious items (Explosives, High density, material narcotics) should be displayed in one mode and that should be on line	Scan the CTP and checked the multi energy X-ray imaging facility through the multi energy test (i.e. sugar & salt) to distinguish inorganic & organic materials with the colours on the VDU.	
20.	Radiation Safety The machine must comply with requirements of health and safety regulations with regard to mechanical electrical and radiation hazards. Before installation of the machine, the supplier/manufacture should furnish relevant certificate from Atomic Energy Regulatory Board of India regarding radiation safety. The company manufacturing the equipment should have ISO certification for manufacturing and servicing of X-ray Screening machines.	AERB certificate be obtained from the Vendors.	

Sl. No	Revised Technical Specifications	Trial Directives	Remarks
21.	Machine should be properly sealed from all the sides for pest proof. Dust proof cover is to be provided for covering when system is not in use.	To be physically checked by BOO.	
22.	Facility for variable contrast must be incorporated to allow enhancement of lighter and darker portion of the image.	Scan the baggage through X-Ray machine and operate the variable contrast key for checking of enhancement of darker portion of the image.	
23.	The machine should be so designed that software enhancement can be easily implemented to take care of new technique in image processing and pattern recognition.	OEM certificate to be obtained.	
24.	Full diagnostic built in test facility. All models should have software controlled diagnosis report facility and system should give printout if printer is connected.	To be physically checked by the BOO.	
25.	All software features of machine should be online and password protected.	To be physically checked by the BOO.	
26.	Machine should be capable for recalling 15 or more previous images.	To be physically checked by the BOO.	
27.	It should have the capability of archiving 3000 or more images with date & time stamp.	To be physically checked by the BOO.	
28.	Control desk with security housing and locking provision should be available. The operator personal identification number can be entered the keyboard along with generation of log.	To be physically checked by the BOO.	
29.	Facility of image enhancement should be available.	Scan the baggage through X-Ray machine and operate the image enhancement key available on the keyboard.	
30.	All models should have online recording facility and images can be recorded in CD R/W or/and USB and should be able to view images so recorded on stand-alone PC.	To be physically checked by the BOO.	
31.	Lead impregnated safety screens should be available at either ends of the tunnel. This should be covered by relevant AERB certificate. Idle rollers to be	AERB certificate to be obtained from the Vendors,	

Sl. No	Revised Technical Specifications	Trial Directives	Remarks
	provided at either ends of the tunnel to facilitate placing of baggage at input and output.		
32.	All software features should be controlled from key board of machine only. Keyboard function should be user friendly. To enable/disable the software features system should not be rebooted	To be physically checked by the BOO.	
33.	If the machine fails to penetrate a particular item then an alarm video and audio both should be generated to notify the operator	To be physically checked by the BOO.	
34.	The threat image projection (TIP) system software to be incorporated in all X-Ray BIS operation as per details given in Annexure-I.	To be physically checked by the BOO as per Annexure-I.	
35.	Copy of all software including X-Ray Software with recovery CD must be provided.	X-Ray software with recovery CD be obtained from the Vendor by the BOO.	
36.	Operational Training- Operating staff has to be provided free training.	A written agreement be obtained from the Vendor by the BOO.	
37.	Operating & service manual shall be provided with each machine.	A written agreement be obtained from the Vendor.	
38.	Other Features a) Edge & variable edge enhancement. b) Inverse Video c) Set up time not more that 10 minutes d) Pseudo colour e) Date & Time display.	The features mentioned at 39(a), (b), (d) & (e) to be physically checked by the BOO after scanning the baggage through X-Ray machine. The feature 39(c) to be physically checked by the BOO. Time should be noted from plugging the machine through electrical component to bring the machine in operation condition.	
39.	Minimum Computer Configuration: - 1. CPU: Should be able to deliver the output to meet the specifications mentioned as above. 2. Hard Disk Drive: 500 GB 7200 rpm serial ATA HDD or Better 3. Mouse: Optical 4. Ports: 6 USB Ports (with at least 2 in Front), 1 Serial Port, 1 Parallel port, 1 PS/2 Keyboard	All features to be checked through technical literature in addition to physical verification.	

Sl. No	Revised Technical Specifications	Trial Directives	Remarks
	and 1 PS2 Mouse Port, audio ports for microphone and headphone in front. 5. CD-R/RW Drive : DVD Writer. 6. Networking facility : 10/100/1000 on board integrated Network Port with remote booting facility remote system installation, remote wake up, out of band management using any standard management software.		
40.	UPS: - 3 KVA or better online with back-up time of ½ hour whole system.	To be physically checked by the BOO.	
	TIPS Feature		
	Threat Image Projection		
01	Tip software facility shall be incorporated in the offered X-ray machine to assist supervisors in testing the operator alertness and training X-ray screeners to improve their ability in identifying specific threat object. The system will create a threat object and the same will be superimposed on the monitor screen while a bag is being screened. To acknowledge that the operator has seen the false object, operator must press the control panel key that will cause the computer generated threat object to disappear from x-rayed bag image on the VDU screen. Each operators action shall be recorded in the hard disc of the computer for the auditing purpose by the supervisor or other authorized person.	To be physically checked by the BOO.	
	DESIGN OF THE SYSTEM:		
02	Tip software should be compatible with other X-ray technologies such as automatic reject unit. Dual X-Ray screen technologies, automatic treat recognition system etc. All x-ray image functions must be available at the same time along with the TIP.	To be physically checked by the BOO.	
	IMAGE LIBRARY		
03	The image library should have an image library containing at least 100 explosives devices, 100 knives and 100 firearms in various sizes, shapes,	To be physically checked by the BOO.	

Sl. No	Revised Technical Specifications	Trial Directives	Remarks
	locations and orientations. However, the system shall have facility to expand the library to incorporate additional images by user without assistance of the manufacture.		
04	The image library should contain images of threats at different orientations both plan and end on orientation should be used. Although these will be assigned different file names and references, it must be possible to cross-reference these as the same threat. All threat image Projection images must be realistic, representative and non distinguishable from real threat items.	To be physically checked by the BOO.	
	<u>TIME INTERVAL</u>		
05	Programming facility shall be available to project threat images in different intervals. The time period for threat image as well as image mix in percentage shall be user programmable e.g. software shall select 40% images of explosive devices, 35% of fire arms & 25% knives or random etc.	To be physically checked by the BOO.	
06	Once the screener has responded to identify the computer generated threat image, it should remain on the screen for a predefined user programmatic feedback message shall be visible to the screener.	To be physically checked by the BOO.	
	<u>SYSTEM ADMINISTRATION</u>		
07	The threat image projection facility shall have details of user data-base such as Department name, screener name, Organization, User ID Number, level of access such screener, administrator, Maintenance & Password etc.	To be physically checked by the BOO.	
08	Access to start up menu should be restricted only to the authorized individuals. A log-in procedure by means of Password" or "Security Key" could achieve restricted access to each of the comment. The log-in procedure should not take longer than 20 seconds. The system should have facility to by pass the TIP facility, if programmed so by the system administrator. It is to be ensured that the TIP software shall not be	To be physically checked by the BOO.	

Sl. No	Revised Technical Specifications	Trial Directives	Remarks
	hindrance to normal functioning of x-ray machines.		
09.	When the operator logs-in or logs-out message should be displayed on x-ray BIS VDU Screen to confirm that the/she has been correctly logged-in or logged-out.	To be physically checked by the BOO.	
	FEED BACK REPORT		
10	The threat image Projection should be capable of giving feedback "HIT,MISS or FALSE ALARM" message. No message will be presented if a screener correctly passed as clear bag.	To be physically checked by the BOO.	
11.	A "HIT" message to be presented when a screener has correctly identified a Threat image Projection Image. A "MISS" : message shall be presented when screener fails to identify the TIP image. A "False Alarm" message shall be given when screener incorrectly indicate TIP image when in fact no threat image projection is present. The feedback should clearly indicate in a screen that a tip object has been correctly identified/tip object has been missed/ that a TIP object has been missed/no TIP object was present. Information should be recorded in the database.	To be physically checked by the BOO.	
12.	Different colour coding shall be used for feedback to the Screener., It is recommended that colour code "Red for MISS" Green for " HIT" and Yellow to False Alarm or interrupt" be used.	To be physically checked by the BOO.	
13.	The system shall automatically prepare the daily log of events for each shift and for each Screener performance. TIP log shall include particulars of Name of Screener, Time & date of threat image, whether threat image was successfully identified or missed etc.	To be physically checked by the BOO.	
14.	The report on Threat Image Projection system may have date and time (From - to) as per requirement. Screener particulars, and decision/out come i.e. MISS, HIT or False Alarm in percentage as well in absolute numbers, numbers of bags screened,	To be physically checked by the BOO.	

Sl. No	Revised Technical Specifications	Trial Directives	Remarks
	categories such as explosives devices knife or weapon etc.		
15.	As a standard practice, daily/weekly /monthly report shall be retrieved. Report shall be for any given time and period, as per command.	To be physically checked by the BOO.	
16.	All data should be stored on the system for a minimum of two months after it has been down loaded. No individual, regardless of access rights to the Threat Image Projection components would delete or amend any of threat images Projection data or time i.e. Threat Image Projection data on the actual X-ray machine will be read only file.	To be physically checked by the BOO.	

तकनीकी विशेषज्ञों के उप समूह द्वारा यह निश्चित किया गया है कि उक्त गुणात्मक आवश्यकता को अधिक बेहतर बनाने के लिए गृह मंत्रालय एवं सीमा सुरक्षा बल की वेबसाईट पर विक्रेताओं/फर्मों के सुझाव प्राप्त करने हेतु 15 दिन के लिए अपलोड किया जाए।

नोट – सभी विक्रेताओं/फर्मों से निवेदन है कि अपने सुझावों के साथ निम्नलिखित कागजात संलग्न कर ई-मेल पता comdtord@bsf.nic.in पर भेजने का श्रम करें:-

1. उत्पाद की वास्तविक विवरण पुस्तिका।
2. उत्पाद की साहित्यिक रचना का ब्यौरा।
3. गुणात्मक आवश्यकताओं के उपर व्यापक टिप्पणीयों।

कपिल चाहरी
20/08/16
(कपिल चाहर)
उप कमांडेण्ट
(आधुनिकीकरण)